

Product information sheet

Product Name: Safety Rider Mini Hump

Models: Safety Rider Mid-Section, Male End Cap, Female End Cap

Manufacturer: GNR Technologies Inc., manufacturing division of Traffic Logix Inc.

990 Upton, Lasalle, QC H8R 2T9

Tel.: (514) 366-6116, Fax: (514) 366-6440

Product Description: Safety Riders of required lengths are constructed using the interlocking

middle and the end cap modules. The standard foot print dimensions of each module are 35.5" by 19.5". The end caps are square with the similar footprint as middle modules. The weight of the middle modules is

36 lbs, the end cap modules are 33 lbs.

Each unit is bolted to a paved road surface using six lag bolts 3/8" dia.

through a plastic shield installed in the road surface.

Dimensions of the

modules:

width 35.5" (+/- 1/16")

length 19.5" (+/- 1/8")

- thickness 2.1" (+/- 1/8")

Dimensions of the

Safety Rider

(the length of the Safety Rider is adjustable):

width 35.5"

length: as required by 19.5" increments

height: 2.1"

Material: Compression molded 100% recycled rubber composite

Physical properties: - tensile strength: minimum 500 psi

shore hardness: minimum 70A

specific gravity 1.1-1.5

Marking: Rubber modules are available in black with yellow or white in-molded reflective tape

Installation Method: - each module is affixed to the pavement with six zinc plated steel lag bolts 3/8" x

4", plastic polypropylene shields and 3/8" zinc plated steel washers supplied with

the modules

- 9/16" diameter holes are drilled through the holes in the modules into a paved

road.

the plastic shields are installed in the mounting holes

- the lag bolts are inserted into mounting holes and tightened

(do not over tighten the bolts)

Installation Tools: - chalk line, measuring tape, heavy duty hummer drill, 9/16" dia. by 10" long

carbide tip drill bits, 11/16" drive socket with a power tool, portable blower, utility

knife, crow bars

additional bolts, shields, and washers can be purchased from GNR Technologies

A three (3) year warranty on the product and a one (1) year warranty on the tape is provided on all Safety Rider components installed as per the manufacturer's Warranty:

installation instructions.

03/06/2011